Rezolin, LLC 131-A7 Business Center Drive Ormond Beach, FL 32174 PH: (386) 677-8238

FX: (386) 677-9072 www.aplusbputty.com **A + B**<sup>®</sup> 9915 Epoxy Paste PRODUCT NUMBER

Page 01 of 03

## TECHNICAL DATA SHEET

# 9915 WHITE A+B® FAST SET EPOXY PASTE SETS IN 5 - 10 MINUTES

## DESCRIPTION

 $A+B^{\circledast}$  9915 WHITE FAST SET EPOXY PASTE is a companion of  $A+B^{\circledast}$  EPOXY PUTTY. It is packaged in handy tubes with an easy one-to-one mix ratio. It is recommended that for those thin film applications, repairing, bonding, filling, and many other applications. Just squeeze out equal amounts of Part A and B, mix, and material is ready for use.

For larger gaps, cracks, areas to be filled, sealed or repaired use A + B<sup>®</sup> Epoxy Putty.

#### **ADVANTAGES**

Can be applied on vertical and overhead surfaces without sagging, running or dripping. Will not shrink.

PHYSICAL PROPERTIES	TEST METHO	D VALUE
Tensile Strength, psi Compressive Strength, psi Bond Strength, psi Coefficient of Thermal Expansion, Maximum Use Temperature, °F	D412 D695 D1002 TMA	3,500 10,000 300 4 x 10 <sup>-5</sup> 250
Hardening Time at 75 °F, minutes Color	D2471	5-10 White
Shrinkage, 75 ° F	D2566	None
ELECTRICAL PROPERTIES		
Dielectric Strength, volts/mil	D-149	300

#### APPLICATION TIPS

- 1. Remove grease, oil or gasoline from area to be repaired. Slightly roughen surface with wire brush or sandpaper.
- 2. Squeeze out equal amounts of Parts A and B.
- 3. Mix Parts A and B until uniform in color.
- 4. After mixing, apply A + B<sup>®</sup> 9915 FAST SET EPOXY PASTE to surface to be repaired.
- 5. Spread mixed paste to a thin, bubble-free film on both sides of matching surfaces. The finished bond thickness should be between 0.005" to 0.010" for best results.

Last Update: September 4, 2003

# **A** + **B**<sup>®</sup> 9915 Epoxy Paste PRODUCT NUMBER

Page 02 of 03

#### FEATURES:

A FAST SET epoxy paste for suggested uses listed below:

# Pool or Spa:

Repairs small cracks or holes in decks and broken tiles

Fill cracks and holes in pool or spa

Use as caulk between tiles and joints

Repair cracks or leaks in porcelain or ceramic fixtures such as tubs, toilets, sinks and tiles

# Home, Office, Plant, and Plumbing:

Sealing plant Compressed air lines

Bonding metal, plastic, copper, PVC, fiberglass, chrome, iron, and tile

Fill small breaks, cracks, or leaks in all types of plumbing fixtures – metal, plastic, copper, PVC, chrome and iron Repair broken fillings on all major appliances

Use as caulking in bathroom or kitchen and as waterproofing or weather stripping around doors and windows

#### Automotive:

Repair small cracks in distributor caps, battery terminals, and cases

Repair small "pot-metal" automotive grills

Repair cracked metal, porcelain, ceramic or plastic parts

Seals all types of cracks and leaks

Insulate electrical cable splices – wire tacking – non conductive

For larger gaps, cracks, areas to be filled, sealed, bonded or repaired use  $A + B^{\otimes}$  Epoxy Putty

## STORAGE:

A+B<sup>®</sup> 9915 should be stored in a cool dry area. Shelf life is a minimum of one year in unopened containers when stored at 65-80°F (one year from date of shipment).

Last Update: September 4, 2003

Page 03 or 03

#### LIMITED WARRANTY AND TERMS

Rezolin, LLC ("Rezolin") warrants that, for a Warranty Period of one year (or the period specified on the applicable Technical Data Sheet, whichever is less) from the date of shipment from Rezolin to the Initial Purchaser, that this Rezolin product was manufactured in accordance with Rezolin's specifications in effect on the date of manufacture. These specifications are available upon request. This Warranty does not cover test data, or any defects, damages of other harms caused to any extent or in any way by failure to follow applicable Rezolin instructions, if any, or abuse or misuse of the product.

WARRANTIES DISCLAIMED – THE WARRANTY STATED IN THE PARAGRAPH ABOVE IS IN PLACE OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED. REZOLIN EXPRESSLY DISCLAIMS ANY OTHER WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. ALTHOUGH REZOLIN MAY HAVE SUGGESTED THE PRODUCT OR DEVELOPED THE PRODUCT AT THE PURCHASER'S REQUEST, IT IS THE PURCHASER'S RESPONSIBILITY TO TEST AND DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE PURCHASER'S INTENDED USE AND PURPOSE, AND PURCHASER ASSUMES ALL RISK AND LIABILITY WHATSOEVER REGARDING SUCH SUITABILITY.

LIMITATIONS OF REMEDIES AND DAMAGES – FOR ANY VALID CLAIM PRESENTED UNDER THE LIMITED WARRANTY, REZOLIN WILL REPLACE THE PRODUCT, OR AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS REPLACEMENT/REFUND REMEDY IS THEPURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST REZOLIN. THE PURCHASER AGREES THAT NO THER REMEDY (INCLUDING BUT NOT LIMITED TO LOST PROFITS, LOST SALES, INJURY TO PERSON OR PROPERTY OR ANY OTHER INCIDENTAL OR CONSEQUENTIAL LOSS) SHALL BE AVAILABLE TO PURCHASER FOR CLAIMS ARISING OUT OF ANY USE OF THE PRODUCT REGARDLESS OF THE LEGAL THEORY (CONTRACT, TORT OR OTHER). IN NO EVENT WILL REZOLIN BE OBLIGATED TO PAY DAMAGES TO PURCHASER IN ANY AMOUNT EXCEEDING THE PRICE THAT THE PURCHASER PAID FOR THE PRODUCT.

<u>LIMITATION OF ACTIONS AND VENUE</u> –Any claim made or action commenced by Purchaser under Rezolin's limited warranty as set forth herein must be brought within one year from the date of shipment from Rezolin to the Purchaser. Purchaser agrees that all disputes arising from Rezolin's sale of product to Purchaser shall be brought if at all, in and before a court located in the State of Florida, to the exclusion of the courts of any other state.

<u>CONDITIONAL ACCEPTANCE</u> – Rezolin's acceptance of Purchaser's order for this product is expressly conditional on Purchaser's assent to terms and conditions set forth herein.

**ADEQUATE TESTS:** The information contained in this bulletin we believe is correct to the best of our knowledge and tests. The recommendations and suggestions herein are made without guarantee or representation as to results. We recommend that adequate tests be made in your laboratory or plant to determine if this product meets all of your requirements.

Last Update: September 4, 2003